

## **Independence Series**

IRW - Internal with Winch Wire Halyard Ground Set Installation

## F Top Diameter Truck and Ornament (Options Available) See Specification Box Wire Cable Assembly and Flag Arrangement Assembly (Stainless Steel Wire Aircraft Cable) **Mounting Height** Two (2) Stainless Steel Swivel Flagsnaps and Two (2) Neoprene Flagsnap Covers Counterweight and Retainer Ring Assembly **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube

Flush Access Door with Keyed Lock, Reinforced Door Frame, Manually Operated Winch (Positive Locking At Any Position), and Removable Winch Handle

## **D** Butt Diameter

Aluminum Collar (Options Available)

See Specification Box Perimeter caulked by Installer

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve 3/16" Steel Support Plate

Lightning Spike -3/4" Diameter Steel Rod Note: Foundation design not included. Foundation dimensions should be determined by a qualified Engineer familiar with site soil conditions.

IRW-GS

**Customer Name:** Dealer:

**B** Depth

Set

6"

2

9

Freedom Flag and Pole Qty: 1

Project: **USDA** Center Location: Alma, WI

Notes:

IRW30C61G-T0Y-O2N-C0W-FSA

## **IRW30C61**





**TRK-9660** 

Int. Revolving Truck Sealed Bearings



BAL-0612-GLD-HD Gold Anodized

Aluminum Ball



COL1-A06S FC-11 Spun Alum 1-Piece



SAT Satin Finish



**IRW - WINCH** Reinforced Welded Door Frame

| Specifications                         |
|--|
| •                                      |
| A. Mounting Height: 30'                |
| B. Set Depth: 3'-0"                    |
| C. Total Length: 33'-0"                |
| D. Butt Diameter: 6"                   |
| E. Wall Thickness: .156"               |
| F. Top Diameter: 3.5"                  |
| Flagpole Sections: 1                   |
| Shaft Weight: 143 lbs.                 |
| Hardware Weight: 22 lbs.               |
| Ground Sleeve Weight: 36 lbs.          |
| * Max Flag Size: 6' x 10'              |
| * Max Wind Speed w/Nylon Flag: 108 mph |
| * Max Wind Speed No Flag: 174 mph      |
|  |
| * Wind Speed Specifications from       |
| ANGUNIAAMM ED 1001 07                  |

| ANSI/NAAMM FP 1001-07

CAFP\_010819\_1pg - 1 -